



**BAXTER
VERTICUT[®]
INC.**
BANDSAW MACHINES

BAXTER SAW MODEL 360SA SEMI-AUTOMATIC BANDSAW



CUTTING CAPACITY	
Round at 0°	14" (360 mm)
Round at 45°	10 ¾" (273 mm)
Rectangular	14" x 19" (360 x 480 mm)
SPECIFICATIONS	
Blade Size	1" x 13'6" (27 x 4115 mm)
Blade Speeds	80, 125, 180, 265, 400 ft/min (25, 38, 55, 81, 122 m/min)
Blade Tension (spring comp.)	30,000 psi (207 MPa)
Blade Guides	Carbide with Rollers
Table Height	26 ¼" (660 mm)
Maximum Work Load	3,000 lb. (1350 kg)
Machine Weight	1,400 lb. (636 kg)
Overall Dimensions	84"x48"x72" (2130x1220x1830 mm)
DRIVE	
Blade Drive	2 HP (1.5 kW)
Hydraulic Drive	1 HP (.75 kW)
Voltages available (three phase)	575, 460, 230 and 208

Standard Features

- Double column machine provides maximum capacity and rigidity
- Design utilizes linear bearings for high stiffness and smooth motion
- Hydraulic lift of the saw head
- Saw up travel can be set to minimize distance between the blade and the top of the material
- Saw down travel can be set to allow notching of blocks
- Semi-automatic cut cycle and manual saw control, saw up, rapid saw down, saw cut
- Cutting feed rate hydraulically adjusted
- Load sensing valve stops the feed if the blade starts to overload, typical cutting structural shapes
- Magnetic motor starter with automatic shut off at the end of cut, motors thermal overload protection
- Power disconnect on machine
- Blade guards and fully enclosed drive belt guard
- Powered blade brush to remove cutting chips
- Quick acting material clamping
- Miter cuts up to 45 degrees by swiveling vise
- Adjustable material length stop for repetitive cutting
- Cast ductile iron wheel
- Blade guides are carbide faced with rollers to remove blade twist and dampen vibration
- Flood coolant system to both saw guides with adjustable flow rates
- Gear box designed for heavy duty bandsaw machines, precision worm shaft on taper roller bearings and phosphorous bronze worm gear set supported on sealed ball bearings, oil bath lubrication
- All bearings are totally enclosed and lubricated for life
- Electric system uses only C.S.A./UL approved components and is electrically approved
- Premium quality bimetal bandsaw blade
- Instruction and parts manual



Model 360SA

Available Options

Variable Speed Drive

Single Phase

Hydraulic Vise

Conveyor (10')

Crating Charges

27 Kenhar Drive, North York, Ontario, Canada M9L 1M9

Tel 416-741-7100 Fax 416-741-7114 email info@verticut.com www.verticut.com

